

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (currently amended) For use with a junction box having a wall with inside and outside surfaces and an opening through said wall, a one-piece, die cast fitting comprising a cylindrical leading end portion that can be inserted into said opening of said junction box, a collar positionable adjacent said outside wall surface of the junction box, two locking fingers spaced 180° apart spreading radially axially outwardly from said leading end portion toward said collar, said locking fingers having free ends that engage said inside wall surface of said junction box when said leading end portion is inserted through said opening, whereby said wall of said junction box is captured between said collar and said free ends of said fingers, [[and]] tensioning fingers adjacent to and on each side of said locking fingers, said tensioning fingers spreading radially axially outwardly from said end portion toward said collar so as to engage the edge of said opening when said end portion has been inserted therein, and notches separating said locking fingers from the adjacent tensioning fingers and forming the edges of adjacent fingers, whereby said fingers can flex to permit said one-piece die cast fitting to be engaged in said opening of said junction box.

2. (currently amended) A one-piece, die cast fitting comprising a cylindrical leading end portion, a radial collar, two locking fingers spaced 180° apart spreading radially axially outwardly from said leading end portion toward said collar, said locking fingers having free ends spaced from said collar, [[and]] tensioning fingers adjacent to and on each side of said locking fingers, said tensioning fingers spreading outwardly from said end portion toward said collar and having free ends that are closer to said collar than said free ends of said locking fingers, and notches separating said locking fingers from the adjacent tensioning fingers and forming the edges of adjacent fingers, whereby said fingers can flex to permit said one-piece die cast fitting to be engaged in an opening of a junction box.

3. (currently amended) A one-piece, die cast fitting comprising a cylindrical end portion, a radial collar, two locking fingers spaced 180° apart that spread outwardly from said cylindrical end portion towards said collar, said locking fingers having free ends that can be flexed radially inwardly toward the axis of said cylindrical end portion, [[and]] tensioning fingers adjacent to and on each side of said locking fingers, said tensioning fingers spreading outwardly from said cylindrical end portion toward said collar, said tensioning fingers being flexible radially inwardly of said cylindrical end portion and having free ends closer to said collar than said free ends of said locking fingers, and notches separating said locking fingers from the adjacent tensioning fingers and forming the edges of adjacent fingers, whereby said fingers can flex to permit said one-piece die cast

Appl. No. 10/669,489  
Amdt. Dated June 25, 2004  
Reply to Office action of April 2, 2004

fitting to be engaged in an opening of a junction box.